

TRACSTAR® 412i

4" IPS - 12" DIPS (110MM - 340MM)



MADE FOR

UNDERGROUND
CONSTRUCTION



The TracStar® /Series technology is now available for medium diameter pipe sizes. The TracStar 412/ incorporates the FusionGuide™ Control System seen on other TracStar /Series models, giving operators the choice of three levels of control during the fusion process. Each level has varying degrees of assistance, from manual control to fully automatic fusion.

Designed to butt fuse pipe sizes from 4" IPS to 12" DIPS (110mm to 340mm), the TracStar 412/ offers a self-contained, self-propelled, track-mounted vehicle that can handle grades up to 30 percent. Its improved cowl design aids in heat dissipation, and its powerful diesel engine allows it to be used on jobsites where gasoline is not permitted.

Like other TracStar /Series machines, the TracStar 412/is controlled via the DataLogger®, McElroy's ruggedized tablet that records fusion parameters and other pertinent data during the fusion process. The TracStar 412/s enhanced guided workflow manages machine pressures, carriage, shift sequence, and more to ensure standards compliance and a successful fusion.

All required fusion operations, including machine pressures, carriage open/close, and shift sequence are controlled using the DataLogger®.

ADDITIONAL IMAGES



STANDARD FEATURES

- ✓ Self-contained, self-propelled, all-terrain
- ✓ Patented Centerline Guidance System for equal distribution of force around the joint
- ✓ Powered by a diesel engine
- ✓ On-board generator for powering heater
- ✓ Thrust-bearing-equipped clamp knobs to minimize force required to clamp and round pipe
- ✓ Removable 3- or 4-jaw carriage for in-ditch use
- ✓ Dual hydraulic pipe lifts aid in loading and unloading pipe
- ✓ Serrated jaws and inserts keep pipe from slipping during fusion
- ✓ Industry-standard semi-automatic hydraulic control system
- ✓ Redesigned cowlings for better airflow and ease of maintenance
- ✓ Battery disconnect for easy lockout
- ✓ 8+ hours operational fuel tank capacity
- ✓ Hydraulic Clamping available
- ✓ ISO-compliant industrial Teflon-coated heater plates
- ✓ Advanced blade design for smooth face and long life
- ✓ Self-locking brakes
- ✓ DataLogger compatible



DataLogger
COMPATIBLE

SEE SECOND PAGE FOR DETAILED SPECIFICATIONS

Copyright © 2026 McElroy Manufacturing, Inc. The contents of this specification page are for informational use only and subject to change without notice. All trademarks are property of McElroy Manufacturing, Inc. unless otherwise noted. All Rights Reserved. 06/03/2026

McELROY

TRACSTAR® 412i

4" IPS - 12" DIPS (110MM - 340MM)

SPECIFICATIONS

| MODELS | | ENGINE | | MOBILITY | |
|------------------------------|--------------------------|---|-------------------------------|----------------------------|----------------------------------|
| AT12P1011815 | High Force | Engine Horse Power | 20 HP | Mobility Type | Rubber crawler tracks |
| AT12P1011819 | Medium Force | Engine Cooling | Liquid Cooling | Transportation | Self-propelled |
| AT12P1011823 | Low Force | Engine Fuel Type | Diesel | Vehicle Speed | 1.5 MPH |
| WEIGHTS | | Engine Fuel Tank Capacity | 5 Gallons (18.9 Liters) | Lifting | Lift points and lifting assembly |
| Machine | 2,089 lbs. (947.6 Kg) | Engine Operational Fuel Tank Capacity | 8 Hours | Starting System | Electric |
| Vehicle | 1,765 lbs. (800.6 Kg) | Engine Starting System | Electric | MACHINE DIMENSIONS | |
| Carriage | 585 lbs. (265.4 Kg) | POWER | | Machine Length | 97.1" (2,466.3mm) |
| Heater | 24 lbs. (10.9 Kg) | Heater | 3,000 Watts, 50 / 60 Hz, 1 Ph | Machine Width | 55.6" (1,412.2mm) |
| Facer | 62 lbs. (28.1 Kg) | Facer | Hydraulic | Machine Height | 55.3" (1,404.6mm) |
| Shipping Weight | 2,200 lbs. (997.9 Kg) | CHASSIS | | CARRIAGE DIMENSIONS | |
| HYDRAULICS | | Frame | Welded steel construction | Length | 44" (1,117.6mm) |
| System Pressure | 2,300 PSI (158.6 BAR) | Brake | Self-locking | Width | 43" (1,092.2mm) |
| Fusion Pressure | 1,500 PSI (103.4 BAR) | INCLUDES | | Height | 29" (736.6mm) |
| Hydraulic Reservoir Capacity | 10 Gallons (37.9 Liters) | Fusion machine, facer, heater, DataLogger tablet, 12" IPS/DIPS Master Inserts and lifting assembly. | | | |